

## CONTAINER EQUIPPED WITH AT LEAST ONE CLOSURE DEVICE

The invention relates to a container that is usable particularly under conditions of weightlessness and is  
5 equipped with at least one closure device.

In zero gravity, any object placed in a container and not attached, floats about. When the container is opened, it therefore tends to escape from the container  
10 freely. This means that great care must be exercised when opening the container (a box, a pocket of a garment, a cupboard) if it contains an object. This problem can be quantified by considering the size of the opening of the container and the number of times  
15 this opening is accessed to open the container. It is therefore most important, in particular when carrying out experiments in zero gravity (or in microgravity) or in the day-to-day life of astronauts under weightless conditions, that objects should not be allowed to  
20 escape so freely from their containers and get in the astronauts' way. Efforts have therefore already been made to solve this problem in the past.

Thus, in this particular field, various container  
25 closure devices are known which are simple to make and use, such as zippers, "Velcro" (registered trademark) or a diaphragm-type device. However, these devices do not keep the object securely in the container and prevent it escaping therefrom because these devices  
30 require deliberate manipulation to open and reclose them (rotation in the case of the diaphragm, translation in the case of the zipper, and touching together of the two parts in the case of "Velcro"). Thus, once opened, these devices do not automatically  
35 reclose to trap the object inside the container. The problem is exacerbated by the fact that under weightless conditions the astronaut is generally using one hand to keep himself still (because he is floating too). He therefore only has one hand to use to open the

container, withdraw (or manipulate) an object contained inside it, and reclose said container.

Patent US-A-2 710 387, which relates to a quite  
5 different field, discloses a closure device for an  
incubator through which the hands can be inserted to  
handle a newborn baby. This device is composed of a  
thin disk of deformable material (such as rubber)  
10 divided into several portions (plates or sectors, for  
example) which can deform in a plane generally  
perpendicular to the closure device (into or out of the  
container) as a hand or an object passes through. To  
introduce an object or a hand into the container, the  
plates are pushed apart into the container to create a  
15 sufficient opening between them. As a rule, once the  
object is in the container and the hand withdrawn, the  
sectors automatically return elastically to their  
closure position to seal the container again. This  
return to the rest state is generally rather slow  
20 because this elasticity must not present too great an  
obstacle to the insertion of the object or hand. To  
withdraw the object from the container, the reverse  
action is carried out, causing the plates to move apart  
elastically out of the container.

25 However, in a hypothetical use under weightless  
conditions, or in any other use in which the container  
may be placed in any position (particularly with its  
opening pointing down) to allow objects to be  
30 manipulated inside it, there is no guarantee with a  
device of that kind that the object will remain in the  
container. For example it may come out if the container  
is disturbed by pressing on the plates. These plates  
may also lose their elasticity over time, and they  
35 often leave large openings around the object (or hand)  
when the object is being inserted, and in the  
particular case of use under weightless conditions, the  
object contained inside the container may then come out

of its own accord, the plates having lost all of their elasticity.

It is therefore an object of the invention to solve  
5 these problems in the context particularly of use under weightless conditions.

To this end, the invention provides a container equipped with a closure device that allows an object to  
10 be placed in said container, particularly for the purposes of manipulating it, or allows it to be withdrawn from said container, the closure device having a plane and comprising closure means that can  
15 deform elastically to change from a closed state of rest under no external stress to an open active state under an external stress, the container being characterized in that said closure means can deform elastically essentially in the plane of the closure device.

20 As a complementary feature, the closure device will comprise at least one rigid peripheral support structure to which are attached the elastically deformable means which intersect each other and  
25 surround a closure member in such a way as to tend to close it.

In particular, the peripheral structure will preferably be a rigid frame on which the elastically deformable  
30 means will then be stretched between two roughly opposite points.

More specifically, the peripheral structure may comprise at least one ring having an inside diameter  
35 and a center, and the elastically deformable means may be elastic bands attached in groups of two juxtaposed elastic bands fixed to the ring at their diametrically opposed ends.

As another feature, the closure member will be a sleeve made of flexible material having a diameter and a length of at least twice this diameter, each end of which sleeve passes through each pair of elastic bands approximately in the center of the ring where it is contracted radially in the closed rest state of the device, or defines a single through opening for the object in the open state of the device, in which state the elastic bands are deformed radially by the passage of said object.

As a complementary feature, one end of the sleeve may be fixed peripherally to an outer face of a second ring and the other end of said sleeve will then be fixed peripherally to an opposite outer face of a first ring identical to the other ring, the sleeve being contracted approximately in a middle zone between each pair of elastic bands, the latter being attached to one or other of the rings which are themselves fixed via their inner faces.

In order to improve the closure of the device and ensure that the object or objects placed in the container do not easily come out again, the two rings will be offset angularly with respect to each other while twisting the sleeve axially, this angular offset being preferably approximately 90°.

As a complementary feature of the invention relating to the making of a self-contained assembly, the rings are held together by adhesive bonding or by stitching.

In accordance with another consideration, the sleeve may be made of fabric.

To ensure that the contraction of the sleeve is effective and equally distributed peripherally, the elastic bands will be eight in number and juxtaposed and attached in pairs distributed in such a way as to

pass through the center of their supporting ring so as to form in the latter eight essentially identical sectors.

- 5 For the same reason, the elastic bands will be slightly under tension on their supporting ring in the closed state of the device.

10 As an another feature of the invention, the shape of the container will be that of a straight or curved cylinder and it will then possess a closure device at each end. In this way the user can insert both hands into the container to manipulate objects placed inside it without the danger that they will escape from said  
15 container.

In order that the user can see the object being manipulated inside the container, the container will include at least a part made of a transparent material.

20 A clearer understanding of the invention and of other characteristics, details and advantages thereof will be gained from a reading of the description which follows, given by way of example with reference to the  
25 accompanying drawings, in which:

- figure 1 is a perspective view of a container in accordance with the invention,
- figure 2 is an end view of a first part of the container closure device,
- 30 - figure 3 is a view similar to figure 2 but with the device in its open state,
- figure 4 is an end view of a second part of the container closure device,
- figure 5 is a cross section through figure 4,
- 35 - figure 6 is a view in cross section through the closure device following assembly and in its closed state, under no external stress, and
- figure 7 is a view similar to figure 6 but with the closure device in its open state.

Figure 1 shows a container 1 that can be used in particular under conditions of weightlessness by astronauts carrying out, for example, experiments in a space station. It takes the form of a long, preferably flexible tube of e.g. fabric, each of its ends 3 and 5 being provided with a closure device 10 as described later. Its body also includes a see-through wall 7 so that the manipulator can see what he is doing inside the container. The user can thus manipulate tools and objects 100 for a zero-gravity experiment, without their escaping from the container during the manipulation or after withdrawal of their hands.

In figure 2, a first support ring 30 belonging to the closure device 10 of the invention is shown. This flat ring 30 of center C and of inside diameter D has a radial part to the inner surface 34 of which are attached the ends 40a of eight elastic bands 40 whose length is slightly greater than D (to enable them to be fixed more easily to this radial part, by adhesive bonding or by stitching, for example). These elastic bands 40 are slightly stretched in their inactive state and intersect each other roughly in the center C of the ring 30, their fixed ends 40a being diametrically opposed. The elastic bands 40 are distributed radially in a regular manner and are attached in four pairs of two elastic bands 40 juxtaposed so as to be parallel and define eight approximately identical sectors.

In Figure 3 it can be seen how these elastic bands 40 can move apart during the introduction of an object (not shown) between each pair of elastic bands, in such a way as to define a through opening 45 that, as closely as possible, matches the shape of said object. The elastic bands 40 of these closure means therefore all deform radially in the plane of the closure device.

In figures 4 and 5, a second support ring 50 for the closure device 10 is shown. This also has an inside

diameter D and a radial part to the outer surface 52 of which is attached a flexible fabric sleeve 60 of diameter D and of length L approximately equal to D, or slightly greater. This sleeve 60 acts as a closure member when working with the elastic bands 40, as will be seen later on in the description.

Figure 6 shows how the two rings 30 and 50, the elastic bands 40 and the sleeve 60 are arranged and connected together axially. Thus, the end 62 of the sleeve 60 is fixed to the outer surface 52 of the second ring, e.g. by hot-melt adhesive bonding or by stitching. The sleeve 60 then passes through the center C of the first ring 30 and passes between each pair of elastic bands 40. It is at this location, roughly in the middle part M of the sleeve, that its diameter D is restricted by the elastic bands 40, such that the closure device 10 is effectively closed. The other end 64 of the sleeve 60 is then stitched or hot-melt bonded to the outer surface 32 of the first ring 30 so that each end of the sleeve 60 is folded out on each side of its middle part M.

To make the device 10 a single unit, the two rings 30 and 50 are then joined to each other (adhesive bonding or stitching) via the inner surface 54 of the second ring and the inner surface 34 of the first ring, preferably after first pivoting them axially with a rotation of about  $90^\circ$  with respect to each other in order to twist the sleeve and improve the closure of the device, by reducing the diameter of the through opening 45.

Figure 7 shows how the middle part M of the sleeve 60 draws back as an object 100 passes through, pushing the elastic bands apart. The opening 45 therefore expands for as long as the object is passing through the sleeve.

Once this assembly has been prepared, all that is left is to fix the outer surface 32 of the first ring 30 to the container 1, as shown in figure 1.

- 5 When an object is to be inserted into the container 1, it has simply to be presented to the center of the closure device 10. By pushing the object (or the hand of the user), the user gradually separates all the elastic bands 40 and the sleeve 60 begins to draw back, offering a larger and larger passage to the object. Because of the structure of the closure device, the elastic bands 40 keep the sleeve 60 always closely around the object being inserted.
- 10
- 15 Varying the tension and the coefficient of elongation of the elastic bands 40 will increase or reduce the ease with which the closure device 10 opens. Objects of near to the inside diameter D of the rings (or of the sleeve) can thus be inserted if the elastic bands are pushed apart as far as they will go. The closure means therefore deform elastically radially when opened, that is to say in the plane of the ring, and not at right angles to the ring, into or out of the container. These elastic bands automatically return to the rest state
- 20
- 25 when under no external stress at all (that is, stress not including their initial tension) once the object is withdrawn from or placed in the container, and the effect of this is to tend to close the sleeve.
- 30 It should however be understood that these examples are provided purely by way of illustration of the subject of the invention, of which they are in no sense a limitation.
- 35 Thus, the number and arrangement of the elastic bands may vary, although it is advisable for the elastic bands of each pair to be close up to each other.



5

10

15

20

25

30

35